

- ITAAB ETS -

1. Introduction

Acacia has downloaded the list of ITAAB Advisory Notes (<http://www.trac.org.uk/itaab/Advisory%20Notes/>) from 048r2 to 119. Most of them apply to layer 1 or don't apply to TTCN source code. A few of them include modification of TestCases of Layer 2 and Layer 3 of TBR3, TBR4, TBR33, TBR34.

Acacia has decided to include in the TBR packages an additional ETS corresponding to an ATS file modified according to the ITAAB advisory notes content.

So Acacia has modify the TBR ATS according to the only ITAAB advisory notes which stipulate modifications of ATS at layer 2 and 3. The criteria to modify the ETSI ATS will be that the modification of the mp code is exactly defined in the ITAAB Note.

2. Liste of Advisory Notes

119	Overshoot protection	NA
118	Error in TBR3 tC TIF4info2 TIF4Info4	NA : Layer1
116	Definition of T_appli1 T_appli2	???
115	Editorial error (safety)	NA
114	Safety	NA
113ra1	TBR requirement (TBR33)	NA
113r1	TBR requirement (TBR33)	NA
111	Connection to Vserie interface	NA
110	Incidence of non-compliance	NA
107	CRC processing Test procedure change	NA (layer 1 PRI)
106	Correction of editorial error TBR33L3 – TC11101	TC11101 of TBR33L3
105	Test methode...Immunity	NA
103	IE checking	NA (for interpretation)
102	Power consumption	NA
101rev1	Clarification on Tes with volume control TBR8	NA
098	Power feeding tests	NA
097	PS1 during testing TBR33	???
096	Categorising ISDN Terminals	NA
095	Shunt terminal v28	NA
094	Timer TWAIT Layer1 ATS	NA (layer1)
092	TE with X21	NA
091	Data rates CTR1 CTR2	NA
090	X21 circuits	NA
088rev1	Postamble checkF1	NA(layer1)
087	Support En-bloc without using SC...	TBR3 TBR4
086r1	Layer2 TC27031	TBR3 4 33 34
085r1	IE checking	NA (for interpretation)
084r1	Layer3 response time in PRI	TBR4 34
083r1	Layer3 default DF69901	TBR3L3
082r1	Connection of the simulator to IUIT	NA
080r1	Use Preferred/Exclusive in RESTART ACK PDU TC19003	TBR3 4 33 34
076r1	BRA L1 for TE unstablestate F3	NA
075r1	CRC4	NA
072r1	TBR-RT applicable to Euro-ISDN....	NA
071r1	TBR-RT applicable to Euro-ISDN....	NA
070r17	CRC processing Test procedure change	NA (layer 1 PRI)
069r1	BRI layer1	NA
068r1	CRC processing and generation of CRC Layer1 PRI	NA
067r1	Testing to be performed on layer1 PRI	NA
066rb3	List of tests and Tcselection Layer3	?????
066ra3	List of tests and Tcselection Layer2	?????
066r3	List of tests and Tcselection Layer2 and 3	?????
063r4	Output jitter of TBR12...	NA
061r2	Electrical characteristics...	NA
060ra2	List of ISDN Layer1 Test....	NA
060r2	Testing ...BRA L1	NA
055r1	Value of the state used in STATUS Message	?????
054rc4	Information about Euro-Numeris...	?????
054rb4	Information about Euro-Numeris...	?????
054ra4	Information about Euro-Numeris...	?????
054r4	Information about Euro-Numeris...	?????
053r2	Preamble PRE_F3_CP Layer1	NA
048r2	Glitch Layer1	NA